



More bad news for termites.

ONLY H2 FOR AREAS OF AUSTRALIA SOUTH OF THE TROPIC OF CAPRICORN

MILL: NO. 555
DATE: 14/01/04
TIME: 13:50:10

APPROVAL No. 635-73 H2
PRESERVATIVE CODE 73
HAZARD CLASS H2S
PENETRATION CODE G/F

HYSPAN H2-S

ONLY H2 FOR AREAS OF AUSTRALIA SOUTH OF THE TROPIC OF CAPRICORN

MILL: NO. 555
DATE: 14/01/04
TIME: 13:50:11

APPROVAL No. 635-73 H2
PRESERVATIVE CODE 73
HAZARD CLASS H2S
PENETRATION CODE G/F





Hyjoist H2-S is death to termites. And now, so is Hyspan H2-S. Both are safely treated with DeterMite™.


It's a safe, odourless treatment applied to the glue-line during manufacture to achieve full termite protection to the core of the beam. Unlike envelope-treated timber, if the surface is damaged or cut on-site, Hyspan® H2-S and Hyjoist® H2-S will still be protected from termites without having to re-apply a preservative. Good news considering the annual cost of termite damage in Australia often exceeds that of fire, flood and storms. You cannot insure against termites, but with our technology you can take effective preventative steps.

The Carter Holt Harvey H2-S range ensures that wherever you use Hyspan H2-S and Hyjoist H2-S from subfloors to roof rafters, it'll be bad news for termites. Good news for you.

PRODUCT SPECIFICATIONS

Treatment: In a revolutionary process, a unique H2-S treatment is applied to the glue-line during manufacture to achieve full termite protection of the beams, from surface to core. The preservative used is DeterMite™

– a synthetic termiticide and insecticide which has low toxicity to humans and to most non-target animal life. It is biodegradable and odourless.



Hyspan H2-S and Hyjoist H2-S termiticide is 'locked-up' in manufacture

Identification: During manufacture Hyspan H2-S is coloured bright yellow for ready identification. It is also clearly marked with the Hyspan H2-S brand.

Structural Properties: The DeterMite™ treatment does not affect the structural properties or dimensions of Hyspan H2-S. For design and specification with Hyspan use designIT software. For a copy, simply call the number below or download it free from our website.

Size Range: The Hyspan range is now available H2-S treated. Four thicknesses: 36mm, 45mm, 63mm and 75mm. Call your distributor for available lengths.

BUILDING STANDARDS*

H2-S treated Hyspan is manufactured to provide termite resistance equivalent to AS1604 Hazard Level 2 for areas of Australia south of the Tropic of Capricorn.

It also conforms to the NSW Timber Marketing Act and the Queensland Timber Utilisation and Marketing Act.



APPLICATIONS

H2-S treatment protects against most termites and other insects, but not fungal decay or rot. It is approved for use in applications which can be described as "interior or protected above ground." This is equivalent to Hazard Level 2 as defined in AS 1604 Specification for Preservative Treatment – Part 3: Plywood, and Part 4: Laminated Veneer Lumber (LVL). It is, therefore, not suitable for situations that will be exposed to weather or dampness such as ground contact.

BENEFITS

- Cost effective protection against termite structural damage.
- Application during manufacture ensures termite protection throughout the product and fixing of treatment.
- Structural properties are unchanged.
- Non-corrosive to nails and fixing plates.
- Safe for users, owners and the environment.
- End cuts, holes and notches do not have to be sealed because the beam is termite protected to the core.
- Odourless.

And as always – defined structural properties which enable confident specification, enhanced workability and consistent performance.

HANDLING & DISPOSAL OF WASTE

Apply standard care and precautions as appropriate for preservative treated timber when handling Hyspan H2-S and Hyjoist H2-S and disposing of off-cuts. For more information contact us for a copy of the Material Safety Data Sheet.

Like all good things, Hyspan H2-S is in demand. Call your distributor for available sizes.

22 Prospect Street
PO Box 425
Box Hill Victoria 3128
Australia

General Enquiries
Freecall 1800 284 792
Facsimile (08) 8739 7313

Technical Enquiries
Freecall 1800 808 131
Telephone (03) 9793 9997
Facsimile (03) 9793 9727

www.chhfuturebuild.com



*For further information see separate guarantee documents.
© February 2007 © Registered Trademarks of Carter Holt Harvey Wood Products Australia Pty Limited ABN 93 002 993 106 Date of Publication February 2007 iezzIE296